HIGH PRESSURE GROUPS

FIRE EXTINGUISHING GROUP



FEATURES

| | HP 50E | HP 50D | |
|--------------|--|--|--|
| Type of pump | Piston Diaphragms | Piston Diaphragms | |
| Pump flow | 50 lpm | 50 lpm | |
| Pressure | 40 bar | 40 bar | |
| Power | Thermal Petrol | Thermal Diesel | |
| Hose length | 40m diam 1/2" | 40m diam 1/2" | |
| Nozzle | Full stream or spraying jet submachine gun | Full stream or spraying jet submachine gun | |
| Price | From 8 415 € | From 11 415 € | |



REEL

Hand-wound hose reel powered by the pump and equipped with 40 meters of flexible \emptyset 1/2" crimped hose.



WATER TANK

Custom-made 12 mm HDPE tank adapted to the shape of the vehicle, equipped with an anti-balan Ball Baffle system, a vent, a visual tank level and a DSP40 filling.





MOTOR PUMP

Piston / diaphragm motor pump connected to the tank including 2 u. 1/2" outlets and equipped with a pressure gauge



Submachine gun type nozzle allowing a full stream or a spraying jet by means of an ergonomic handle.



Custom-made aluminum profile frame with extension for loading by forklift truck and equipped with attachment points for Pickup skips.

